


TORQUE CONTROL SCREWDRIVERS

The **US-LT series** Screwdrivers offer the most advanced design and engineering concepts ever brought together. Accuracy, durability, comfort, simplicity and flexibility will be some of the benefits you will experience with their use.

STRAIGHT TYPE



SPECIFICATIONS

Recommended Air Pressure: 0.6MPa(85psi)

Model	Capacity (Screw Size)		Torque Range		Free Speed (Approx.) rpm	Overall Length (about)		Weight less Bit (about)		From Center to Outside (about)		Air Hose Size (inside Dia.)		Average Air Consumption		Noise Level dB(A)
	mm	in	Nm	in-lbs		mm	in	kg	lb	mm	in	mm	in	m ³ /min	ft ³ /min	
US-LT10B	2.6	7/64	0.20-0.60	1.8-5.3	1000	190	7 31/64	0.29	0.63	12.0	31/64	6.35	1/4	0.15	5.2	75
US-LT20A(B)-26	2.2	3/32	0.15-0.35	1.3-3.1	2600	180	7 3/32	0.34	0.68	13.0	33/64	6.35	1/4	0.16	5.6	71
US-LT20A(B)-18	2.6	7/64	0.25-0.70	2.2-6.2	1800	180	7 3/32	0.34	0.68	13.0	33/64	6.35	1/4	0.16	5.6	70
US-LT20A(B)-10	3	1/8	0.35-1.10	3.1-9.68	1000	180	7 3/32	0.34	0.68	13.0	33/64	6.35	1/4	0.16	5.6	70
US-LT30A(B)-23	3	1/8	0.40-1.00	3.5-8.8	2300	187	7 23/64	0.43	0.94	15.5	39/64	6.35	1/4	0.20	7.0	71
US-LT30A(B)-17	3.5	9/64	0.70-1.50	6.2-13.2	1700	187	7 23/64	0.43	0.94	15.5	39/64	6.35	1/4	0.20	7.0	70
US-LT30A(B)-11	4	5/32	1.10-2.10	9.7-18.5	1100	187	7 23/64	0.43	0.94	15.5	39/64	6.35	1/4	0.20	7.0	70
US-LT40A(B)-21	4	5/32	1.00-1.70	6.2-15.0	2100	209	8 15/64	0.65	1.43	16.5	41/64	6.35	1/4	0.30	10.5	74
US-LT40A(B)-15	4	5/32	1.00-2.20	6.2-19.4	1500	209	8 15/64	0.65	1.43	16.5	41/64	6.35	1/4	0.30	10.5	70
US-LT40A(B)-08	5	13/64	1.60-4.00	14.1-35.2	800	209	8 15/64	0.65	1.43	16.5	41/64	6.35	1/4	0.30	10.5	70
US-LT50B-17	4-5	5/32-13/64	1.50-2.60	9.7-23.0	1700	240	9 29/64	1.00	2.20	19.5	49/64	9.50	3/8	0.50	17.5	75
US-LT50B-08	5-6	13/64-15/64	3.00-5.50	26.4-48.4	800	240	9 29/64	1.00	2.20	19.5	49/64	9.50	3/8	0.50	17.5	75
US-LT50B-05	5-6	13/64-15/64	5.00-10.5	44.0-92.4	480	240	9 29/64	1.00	2.20	19.5	49/64	9.50	3/8	0.50	17.5	74
US-LT30A(B)L-23	3	1/8	0.40-1.00	3.52-8.8	2300	229	8 15/64	0.53	1.16	15.0	19/32	6.35	1/4	0.20	5.2	71
US-LT30A(B)L-17	3.5	9/64	0.70-1.50	6.2-13.2	1700	229	8 15/64	0.53	1.16	15.0	19/32	6.35	1/4	0.20	5.2	70
US-LT30A(B)L-11	3.5	9/64	1.10-2.10	9.7-18.5	1100	229	8 15/64	0.53	1.16	15.0	19/32	6.35	1/4	0.20	5.2	70
US-LT40BL-21	4	5/32	1.00-1.70	8.8-15.0	2100	249	9 25/32	0.70	1.54	17.0	21/32	6.35	1/4	0.30	5.6	74
US-LT40A(B)L-15	4	5/32	1.00-2.20	8.8-19.4	1500	249	9 25/32	0.70	1.54	17.0	21/32	6.35	1/4	0.30	5.6	70
US-LT40BL-08	5	3/16	1.60-4.00	14.1-35.2	800	249	9 25/32	0.70	1.54	17.0	21/32	6.35	1/4	0.30	5.6	70

Air Inlet Size : NPT1/4"

Hex. Size of Bit : 5mm (13/64") for A-Type
6.35mm (1/4") for B-Type